






**Product Dimensions**


**Adjustable and Side Mount Adjustable Mounting**



**Fixed Clip Mounting**



**Mounting and Powerfeed options.**



Top view. End Feed is Solid Line. Back Feed is Dashed Line. For SMLF Mounting flip the outputs in the figures above.

**Finish Options**

- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Non Silver Anodized finishes may have extended lead times.
- Custom RALs are available, please consult Inside Sales with specific request.

**Silver Anodized**



Silver Anodized is a soft silver with a clear finish.

**Black**



Black is a true deep black with a glossy finish.

**Bronze**



Bronze is a rich, dark brown with a satin finish.

**White**







White is a polar bright white and field paintable.





**Powerfeeds and Connectors**

**Linking and Extension Cable Options**





For use with Warm Dim (WD68):







For use with Dynamic White (DW68), RGB Pixel (RGBX18) and RGBW Pixel (RGBWX18):









For use with RGB (RGB42):



For use with RGBW (RGBW36):




**Powerfeeds Position/Type**




Side and Back feeds shown as dashed lines  
All wires are 18 AWG unless otherwise specified

**Sample Layout**



**Lens Option / Light Transmission**


Output Options	Lens/Accessory	
	Wash	
WD68SO - 27K	ND	
WD68SO - 19K	ND	
DW68SO (All On)	ND	
DW68SO (1-Channel)	ND	
DW68HO (All On)	ND	
DW68HO (1-Channel)	ND	
RGBW36SO	ND	
RGBW36HO	ND	
RGB42SO	ND	
RGB42HO	ND	
RGBWX18SO	SD	
RGBX18SO	SD	



**CD SD ND**  
**CD** - Clear Dotting  
**SD** - Slight Dotting  
**ND** - No Dotting

**Accessory Options**

**LVSP-4T-BK**  
 Low Voltage, 4 Terminal Splice Box, Black





**Power Consumption**

Tested at Full Power with PDC Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

**Warm Dim (WD68)**

Nominal Length (in)	End Feed Actual Length	Watts	Nominal Length (in)	End Feed Actual Length	Watts	Nominal Length (in)	End Feed Actual Length	Watts
		SO			SO			SO
<b>12</b>	10 12/16	4.6	<b>47</b>	—	—	<b>82</b>	—	—
<b>13</b>	—	—	<b>48</b>	47 11/16	21.0	<b>83</b>	82 2/16	34.8
<b>14</b>	13 4/16	5.8	<b>49</b>	—	—	<b>84</b>	—	—
<b>15</b>	—	—	<b>50</b>	—	—	<b>85</b>	84 9/16	35.7
<b>16</b>	15 11/16	6.9	<b>51</b>	50 2/16	22.0	<b>86</b>	—	—
<b>17</b>	—	—	<b>52</b>	—	—	<b>87</b>	—	—
<b>18</b>	—	—	<b>53</b>	52 9/16	23.0	<b>88</b>	87 1/16	36.7
<b>19</b>	18 2/16	8.0	<b>54</b>	—	—	<b>89</b>	—	—
<b>20</b>	—	—	<b>55</b>	—	—	<b>90</b>	89 8/16	37.6
<b>21</b>	20 10/16	9.1	<b>56</b>	55 1/16	24.1	<b>91</b>	—	—
<b>22</b>	—	—	<b>57</b>	—	—	<b>92</b>	91 15/16	38.6
<b>23</b>	—	—	<b>58</b>	57 8/16	25.1	<b>93</b>	—	—
<b>24</b>	23 1/16	10.2	<b>59</b>	—	—	<b>94</b>	—	—
<b>25</b>	—	—	<b>60</b>	60	26.1	<b>95</b>	94 7/16	39.6
<b>26</b>	25 8/16	11.3	<b>61</b>	—	—	<b>96</b>	—	—
<b>27</b>	—	—	<b>62</b>	—	—	<b>97</b>	96 14/16	40.5
<b>28</b>	28	12.3	<b>63</b>	62 7/16	27.1	<b>98</b>	—	—
<b>29</b>	—	—	<b>64</b>	—	—	<b>99</b>	—	—
<b>30</b>	—	—	<b>65</b>	64 14/16	28.0	<b>100</b>	99 6/16	41.4
<b>31</b>	30 7/16	13.4	<b>66</b>	—	—	<b>101</b>	—	—
<b>32</b>	—	—	<b>67</b>	—	—	<b>102</b>	101 13/16	42.2
<b>33</b>	32 15/16	14.5	<b>68</b>	67 6/16	29.0	<b>103</b>	—	—
<b>34</b>	—	—	<b>69</b>	—	—	<b>104</b>	—	—
<b>35</b>	—	—	<b>70</b>	69 13/16	30.0	<b>105</b>	104 4/16	43.0
<b>36</b>	35 6/16	15.6	<b>71</b>	—	—	<b>106</b>	—	—
<b>37</b>	—	—	<b>72</b>	—	—	<b>107</b>	106 12/16	43.9
<b>38</b>	37 13/16	16.7	<b>73</b>	72 4/16	30.9	<b>108</b>	—	—
<b>39</b>	—	—	<b>74</b>	—	—	<b>109</b>	—	—
<b>40</b>	—	—	<b>75</b>	74 12/16	32.0	<b>110</b>	109 3/16	44.8
<b>41</b>	40 5/16	17.8	<b>76</b>	—	—	<b>111</b>	—	—
<b>42</b>	—	—	<b>77</b>	—	—	<b>112</b>	111 10/16	45.8
<b>43</b>	42 12/16	18.9	<b>78</b>	77 3/16	33.1	<b>113</b>	—	—
<b>44</b>	—	—	<b>79</b>	—	—	<b>114</b>	—	—
<b>45</b>	—	—	<b>80</b>	79 11/16	33.9	<b>115</b>	114 2/16	46.6
<b>46</b>	45 3/16	20.0	<b>81</b>	—	—	<b>116</b>	—	—

**Power Consumption**

Tested at Full Power with PDC Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

**Dynamic White (DW68)**

Nominal Length (in)	Actual Length	Watts		Nominal Length (in)	Actual Length*	Watts		Nominal Length (in)	Actual Length	Watts	
		SO	HO			SO	HO			SO	HO
<b>12</b>	10 12/16	4.6	5.9	<b>47</b>	—	—	—	<b>82</b>	—	—	—
<b>13</b>	—	—	—	<b>48</b>	47 11/16	18.3	23.1	<b>83</b>	82 2/16	29.9	37.3
<b>14</b>	13 4/16	4.6	5.9	<b>49</b>	—	—	—	<b>84</b>	—	—	—
<b>15</b>	—	—	—	<b>50</b>	—	—	—	<b>85</b>	84 9/16	30.5	38.5
<b>16</b>	15 11/16	5.9	7.4	<b>51</b>	50 2/16	19.0	24.0	<b>86</b>	—	—	—
<b>17</b>	—	—	—	<b>52</b>	—	—	—	<b>87</b>	—	—	—
<b>18</b>	—	—	—	<b>53</b>	52 9/16	20.0	25.4	<b>88</b>	87 1/16	31.4	39.5
<b>19</b>	18 2/16	6.7	8.4	<b>54</b>	—	—	—	<b>89</b>	—	—	—
<b>20</b>	—	—	—	<b>55</b>	—	—	—	<b>90</b>	89 8/16	32.7	40.9
<b>21</b>	20 10/16	7.9	9.8	<b>56</b>	55 1/16	20.7	26.3	<b>91</b>	—	—	—
<b>22</b>	—	—	—	<b>57</b>	—	—	—	<b>92</b>	91 15/16	33.6	41.8
<b>23</b>	—	—	—	<b>58</b>	57 8/16	21.8	27.7	<b>93</b>	—	—	—
<b>24</b>	23 1/16	8.7	10.8	<b>59</b>	—	—	—	<b>94</b>	—	—	—
<b>25</b>	—	—	—	<b>60</b>	60	22.5	28.6	<b>95</b>	94 7/16	34.9	43.3
<b>26</b>	25 8/16	9.8	12.3	<b>61</b>	—	—	—	<b>96</b>	—	—	—
<b>27</b>	—	—	—	<b>62</b>	—	—	—	<b>97</b>	96 14/16	35.8	44.2
<b>28</b>	28	10.6	13.3	<b>63</b>	62 7/16	23.7	29.8	<b>98</b>	—	—	—
<b>29</b>	—	—	—	<b>64</b>	—	—	—	<b>99</b>	—	—	—
<b>30</b>	—	—	—	<b>65</b>	64 14/16	24.6	30.6	<b>100</b>	99 6/16	36.4	44.8
<b>31</b>	30 7/16	11.8	14.8	<b>66</b>	—	—	—	<b>101</b>	—	—	—
<b>32</b>	—	—	—	<b>67</b>	—	—	—	<b>102</b>	101 13/16	37.4	45.7
<b>33</b>	32 15/16	12.6	15.8	<b>68</b>	67 6/16	25.4	31.3	<b>103</b>	—	—	—
<b>34</b>	—	—	—	<b>69</b>	—	—	—	<b>104</b>	—	—	—
<b>35</b>	—	—	—	<b>70</b>	69 13/16	26.7	32.4	<b>105</b>	104 4/16	38.0	46.3
<b>36</b>	35 6/16	13.4	16.8	<b>71</b>	—	—	—	<b>106</b>	—	—	—
<b>37</b>	—	—	—	<b>72</b>	—	—	—	<b>107</b>	106 12/16	39.0	47.2
<b>38</b>	37 13/16	14.5	18.3	<b>73</b>	72 4/16	27.6	33.1	<b>108</b>	—	—	—
<b>39</b>	—	—	—	<b>74</b>	—	—	—	<b>109</b>	—	—	—
<b>40</b>	—	—	—	<b>75</b>	74 12/16	28.4	34.3	<b>110</b>	109 3/16	39.7	47.8
<b>41</b>	40 5/16	15.3	19.3	<b>76</b>	—	—	—	<b>111</b>	—	—	—
<b>42</b>	—	—	—	<b>77</b>	—	—	—	<b>112</b>	111 10/16	40.3	48.9
<b>43</b>	42 12/16	16.4	20.7	<b>78</b>	77 3/16	28.9	35.2	<b>113</b>	—	—	—
<b>44</b>	—	—	—	<b>79</b>	—	—	—	<b>114</b>	—	—	—
<b>45</b>	—	—	—	<b>80</b>	79 11/16	29.5	36.4	<b>115</b>	114 2/16	40.8	49.7
<b>46</b>	45 3/16	17.2	21.7	<b>81</b>	—	—	—	<b>116</b>	—	—	—

**Power Consumption**

Tested at Full Power with PDC Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

**RGB/RGBW (RGB42/RGBW36)**

Nominal Length (in)	Actual Length	Watts		Nominal Length (in)	Actual Length	Watts		Nominal Length (in)	Actual Length	Watts	
		RGBW36	RGB42			RGBW36	RGB42			RGBW36	RGB42
		SO	SO			SO	SO			SO	SO
<b>12</b>	10 12/16	4.0	4.4	<b>47</b>	46 3/16	14.4	16.8	<b>82</b>	81 10/16	26.1	29.4
<b>13</b>	12 12/16	4.0	4.4	<b>48</b>	—	—	—	<b>83</b>	—	—	—
<b>14</b>	—	—	—	<b>49</b>	48 3/16	15.1	17.5	<b>84</b>	83 10/16	26.8	30.0
<b>15</b>	14 11/16	4.5	5.2	<b>50</b>	—	—	—	<b>85</b>	—	—	—
<b>16</b>	—	—	—	<b>51</b>	50 2/16	15.8	18.3	<b>86</b>	85 9/16	27.4	30.7
<b>17</b>	16 11/16	5.1	5.9	<b>52</b>	—	—	—	<b>87</b>	—	—	—
<b>18</b>	—	—	—	<b>53</b>	52 2/16	16.4	18.9	<b>88</b>	87 9/16	28.0	31.4
<b>19</b>	18 10/16	5.6	6.7	<b>54</b>	—	—	—	<b>89</b>	—	—	—
<b>20</b>	—	—	—	<b>55</b>	54 1/16	17.0	19.6	<b>90</b>	89 8/16	28.6	32.2
<b>21</b>	20 10/16	6.2	7.4	<b>56</b>	—	—	—	<b>91</b>	—	—	—
<b>22</b>	—	—	—	<b>57</b>	56 1/16	17.6	20.3	<b>92</b>	91 8/16	29.2	32.9
<b>23</b>	22 9/16	6.7	8.2	<b>58</b>	—	—	—	<b>93</b>	—	—	—
<b>24</b>	—	—	—	<b>59</b>	58	18.2	21.0	<b>94</b>	93 7/16	29.9	33.6
<b>25</b>	24 9/16	7.3	8.9	<b>60</b>	60	18.9	21.7	<b>95</b>	—	—	—
<b>26</b>	—	—	—	<b>61</b>	—	—	—	<b>96</b>	95 7/16	30.2	34.0
<b>27</b>	26 8/16	8.0	9.6	<b>62</b>	61 15/16	19.5	22.4	<b>97</b>	—	—	—
<b>28</b>	—	—	—	<b>63</b>	—	—	—	<b>98</b>	97 6/16	30.8	34.7
<b>29</b>	28 8/16	8.6	10.4	<b>64</b>	63 15/16	20.2	23.2	<b>99</b>	—	—	—
<b>30</b>	—	—	—	<b>65</b>	—	—	—	<b>100</b>	99 6/16	31.3	35.4
<b>31</b>	30 7/16	9.3	11.1	<b>66</b>	65 14/16	20.8	24.0	<b>101</b>	—	—	—
<b>32</b>	—	—	—	<b>67</b>	—	—	—	<b>102</b>	101 5/16	31.9	36.0
<b>33</b>	32 7/16	9.7	11.5	<b>68</b>	67 14/16	21.5	24.7	<b>103</b>	—	—	—
<b>34</b>	—	—	—	<b>69</b>	—	—	—	<b>104</b>	103 5/16	32.4	36.7
<b>35</b>	34 6/16	10.3	12.2	<b>70</b>	69 13/16	22.1	25.5	<b>105</b>	—	—	—
<b>36</b>	—	—	—	<b>71</b>	—	—	—	<b>106</b>	105 4/16	32.9	37.3
<b>37</b>	36 6/16	11.0	13.0	<b>72</b>	71 13/16	22.8	26.3	<b>107</b>	—	—	—
<b>38</b>	—	—	—	<b>73</b>	—	—	—	<b>108</b>	107 4/16	33.5	38.0
<b>39</b>	38 5/16	11.7	13.7	<b>74</b>	73 12/16	23.5	26.9	<b>109</b>	—	—	—
<b>40</b>	—	—	—	<b>75</b>	—	—	—	<b>110</b>	109 3/16	34.0	38.6
<b>41</b>	40 5/16	12.4	14.5	<b>76</b>	75 12/16	24.1	27.6	<b>111</b>	—	—	—
<b>42</b>	—	—	—	<b>77</b>	—	—	—	<b>112</b>	111 2/16	34.8	39.3
<b>43</b>	42 4/16	13.1	15.2	<b>78</b>	77 11/16	24.8	28.2	<b>113</b>	—	—	—
<b>44</b>	—	—	—	<b>79</b>	—	—	—	<b>114</b>	113 2/16	35.6	39.9
<b>45</b>	44 4/16	13.8	16.0	<b>80</b>	79 11/16	25.4	28.8	<b>115</b>	—	—	—
<b>46</b>	—	—	—	<b>81</b>	—	—	—	<b>116</b>	115 1/16	36.3	40.6

**Power Consumption**

Tested at Full Power with PDC Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

**PIXEL**

Nominal Length (in)	Actual Length	Watts		Nominal Length (in)	Actual Length	Watts		Nominal Length (in)	Actual Length	Watts	
		RGBX18	RGBWX18			RGBX18	RGBWX18			RGBX18	RGBWX18
		SO	SO			SO	SO			SO	SO
<b>12</b>	8 13/16	4.6	5.7	<b>47</b>	–	–	–	<b>82</b>	–	–	–
<b>13</b>	12 12/16	4.6	5.7	<b>48</b>	–	–	–	<b>83</b>	–	–	–
<b>14</b>	–	–	–	<b>49</b>	48 3/16	17.4	21.9	<b>84</b>	83 10/16	29.8	37.1
<b>15</b>	–	–	–	<b>50</b>	–	–	–	<b>85</b>	–	–	–
<b>16</b>	–	–	–	<b>51</b>	–	–	–	<b>86</b>	–	–	–
<b>17</b>	16 11/16	6.1	7.5	<b>52</b>	–	–	–	<b>87</b>	–	–	–
<b>18</b>	–	–	–	<b>53</b>	52 2/16	18.9	23.7	<b>88</b>	87 9/16	31.1	38.7
<b>19</b>	–	–	–	<b>54</b>	–	–	–	<b>89</b>	–	–	–
<b>20</b>	–	–	–	<b>55</b>	–	–	–	<b>90</b>	–	–	–
<b>21</b>	20 10/16	7.6	9.4	<b>56</b>	–	–	–	<b>91</b>	–	–	–
<b>22</b>	–	–	–	<b>57</b>	56 1/16	20.3	25.4	<b>92</b>	91 8/16	32.4	40.3
<b>23</b>	–	–	–	<b>58</b>	–	–	–	<b>93</b>	–	–	–
<b>24</b>	–	–	–	<b>59</b>	–	–	–	<b>94</b>	–	–	–
<b>25</b>	24 9/16	9.1	11.3	<b>60</b>	60	21.7	27.1	<b>95</b>	–	–	–
<b>26</b>	–	–	–	<b>61</b>	–	–	–	<b>96</b>	95 7/16	33.4	41.6
<b>27</b>	–	–	–	<b>62</b>	–	–	–	<b>97</b>	–	–	–
<b>28</b>	–	–	–	<b>63</b>	–	–	–	<b>98</b>	–	–	–
<b>29</b>	28 8/16	10.6	13.2	<b>64</b>	63 15/16	23.0	28.8	<b>99</b>	–	–	–
<b>30</b>	–	–	–	<b>65</b>	–	–	–	<b>100</b>	99 6/16	34.6	43.2
<b>31</b>	–	–	–	<b>66</b>	–	–	–	<b>101</b>	–	–	–
<b>32</b>	–	–	–	<b>67</b>	–	–	–	<b>102</b>	–	–	–
<b>33</b>	32 7/16	11.7	14.6	<b>68</b>	67 14/16	24.4	30.5	<b>103</b>	–	–	–
<b>34</b>	–	–	–	<b>69</b>	–	–	–	<b>104</b>	103 5/16	35.9	44.8
<b>35</b>	–	–	–	<b>70</b>	–	–	–	<b>105</b>	–	–	–
<b>36</b>	–	–	–	<b>71</b>	–	–	–	<b>106</b>	–	–	–
<b>37</b>	36 6/16	13.1	16.5	<b>72</b>	71 13/16	25.8	32.3	<b>107</b>	–	–	–
<b>38</b>	–	–	–	<b>73</b>	–	–	–	<b>108</b>	107 4/16	37.2	46.4
<b>39</b>	–	–	–	<b>74</b>	–	–	–	<b>109</b>	–	–	–
<b>40</b>	–	–	–	<b>75</b>	–	–	–	<b>110</b>	–	–	–
<b>41</b>	40 5/16	14.6	18.3	<b>76</b>	75 12/16	27.1	33.9	<b>111</b>	–	–	–
<b>42</b>	–	–	–	<b>77</b>	–	–	–	<b>112</b>	111 2/16	38.4	48.0
<b>43</b>	–	–	–	<b>78</b>	–	–	–	<b>113</b>	–	–	–
<b>44</b>	–	–	–	<b>79</b>	–	–	–	<b>114</b>	–	–	–
<b>45</b>	44 4/16	16.0	20.1	<b>80</b>	79 11/16	28.4	35.5	<b>115</b>	–	–	–
<b>46</b>	–	–	–	<b>81</b>	–	–	–	<b>116</b>	115 1/16	39.7	49.6

**Voltage Drop Calculator**

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
<b>5</b>	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
<b>10</b>	544.1	342.2	215.1	135.3	85.1	53.5	33.7
<b>15</b>	362.7	228.1	143.4	90.2	56.7	35.7	22.4
<b>20</b>	272.0	171.1	107.6	67.7	42.6	26.8	16.8
<b>25</b>	217.6	136.9	86.1	54.1	34.0	21.4	13.5
<b>30</b>	181.4	114.1	71.7	45.1	28.4	17.8	11.2
<b>35</b>	155.5	97.8	61.5	38.7	24.3	15.3	9.6
<b>40</b>	136.0	85.5	53.8	33.8	21.3	13.4	8.4
<b>45</b>	120.9	76.0	47.8	30.1	18.9	11.9	7.5
<b>50</b>	108.8	68.4	43.0	27.1	17.0	10.7	6.7
<b>55</b>	98.9	62.2	39.1	24.6	15.5	9.7	6.1
<b>60</b>	90.7	57.0	35.9	22.6	14.2	8.9	5.6
<b>65</b>	83.7	52.6	33.1	20.8	13.1	8.2	5.2
<b>70</b>	77.7	48.9	30.7	19.3	12.2	7.6	4.8
<b>75</b>	72.5	45.6	28.7	18.0	11.3	7.1	4.5
<b>80</b>	68.0	42.8	26.9	16.9	10.6	6.7	4.2
<b>85</b>	64.0	40.3	25.3	15.9	10.0	6.3	4.0
<b>90</b>	60.5	38.0	23.9	15.0	9.5	5.9	3.7
<b>96</b>	56.7	35.6	22.4	14.1	8.9	5.6	3.5

## Power Supplies


See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view luminii website for list of compatible dimmers.

### For use with Warm Dim, WD68

#### Triac, MLV, & ELV Compatible Dimmers

MODEL	POWER	OUTPUT
PDC - (IP20) Power Supply	96 - 96 Watts	24 - 24 VDC

MODELS	96W
Length	8.25"
Width	4.10"
Depth	1.56"




### For use with Dynamic White, DW68

#### 0-10V Warm Dimming 0% Power Supply 120VAC - 277VAC (for warm dimming of Dynamic White option)

MODEL	POWER	OUTPUT
PS010WD - 0-10 Warm dim LED Power Supply	96 - 96 Watt	24 - 24 VDC

Requires a 0-10V controller to work properly




#### 0-10V Tunable White 0% Dimming Power Supply 120VAC - 277VAC (for tunable white control of Dynamic White option)

MODEL	POWER	OUTPUT
PS010TW - 0-10 Tunable White LED Driver	96 - 96 Watt	24 - 24 VDC

Requires two 0-10V controllers to work properly


MODELS	PS010TW
A Length	14.40"
B Width	2.60"
C Depth	5.20"



#### Customizable Dim to Warm or Variable White via 0 - 10V (for tunable white or warm dimming control of Dynamic option)

MODEL	POWER	OUTPUT	CONTROL
PS010V-0-10 LED Driver	96-96 Watt	24-24 VDC	WW- Standard One Channel - Dim To Warm Curve W2C- Standard Two Channel - Dim 1: Intensity; Dim 2: CCT W21- Standard Two Channel - Dim 1: Warm Channel Intensity; Dim 2: Cool Channel Intensity W1X- Custom One Channel - Dim To Warm Curve W2X- Custom two Channel - Dim 1: Intensity; Dim 2: CCT

Requires a 0-10V controller to work properly




### For use with RGB/RGBW/Pixel, RGB42/RGBW36/RGBX18/RGBWX18

#### Non-Dimming Power Supply 120VAC - 277VAC

MODEL	POWER	OUTPUT	DIMMING	LOCATION
PSV - PSV Series	96 - 96 Watt	24 - 24 VDC	ND - Non Dimming	D - Dry location

Requires a controller and a decoder to work properly

MODELS	96W
A Length	14.40"
B Width	5.20"
Depth	2.60"



## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.



### For use with RGB/RGBW, RGB42/RGBW36 or with Dynamic White, DW68

#### DMX 0% Dimming Power Supplies 120VAC - 277VAC

MODEL	POWER	OUTPUT
PSDMX-DMX Power Supply dims down to 0%	96 - 96 Watt 3X96 - 3 X 96 Watt	24-24 VDC

Features eldoLED's LINEARdrive configurable dimmable drivers.


DDMX-RGBW DMX Decoder not required when purchasing this power supply.



MODELS	96W	3X96
<b>A Length</b>	14.40"	15.75"
<b>B Width</b>	5.20"	6.62"
<b>Depth</b>	2.60"	4.95"

## DMX-1Z-RGBW, DMX-3Z-RGBW

RGBW LED 1 or 3 Zone Controller



DMX /Wireless RGB-W wall-mount controller controls DMX lighting fixtures, wireless control of RGB-W lighting fixture or use both simultaneously. Fits in any standard US switch box. Includes all the outputs in the back of the controller.

Control brightness levels with a single touch, personalize and memorize 3 different scenes, and even create 3 variations of white.

#### Features

- 2 in 1 in-Wall Controller: DMX Control or Wireless RGB-W
- 65,000 Color Options, Dimming and Speed Control
- Memory Function
- 50 Foot Wireless Range
- Easily Fits Standard US Switch Boxes
- Touch Sensitive Glass Surface
- Includes 10 Built in Programs, or Create and Play Your Own

#### Operating Voltage

12 - 24V DC

#### Color Parameters


- Brightness
- Saturation
- Primary colors
- Fading
- Color changing speed

#### ORDERING CODE

MODEL	ZONES	COLOR
DMX - DMX Controller	3Z - Three Zone 1Z - One Zone	RGBW - Red, Green, Blue, & White

## Touch DMX Controller

Touchscreen digital LED controller



MODEL

**TSDMX-E**

TSDMX-E - Touchscreen DMX controller

Programmable advanced DMX512 lighting controller featuring a touch-screen interface. Operates as stand alone controller or integrated with most architectural lighting control systems. Can controller endless DMX512 enabled devices.

Mounts to standard single or dual gang wall box with the included power supply inside the junction box. Terminal block design for power and data connections.

### Features

- Sleek glass design which sits 0.43" from the wall
- Graphical color display to show selected environment
- Color/dimmer/speed palette
- Color temperature mixing
- Touch sensitive buttons. No mechanical parts
- Touch sensitive wheel allows for accurate color selection
- Multi-zone microSD memory
- Multi-room control with 500 scenes, 10 zones
- 1024 DMX channels. Control 340 RGB fixtures
- USB & Ethernet connectivity for programming and control

### Power Supply

7 VDC (included)

### Programmability

PC, Mac, Tablet, Smartphone

### Output Signal


DMX512 (1024 channels)

### Color Parameters

- Brightness
- Saturation
- Speed of color changing sequence
- Fading / dimming / brightness

## DMX Decoder

DMX signal to RGBW decoder (required to operate DMX controller)



ORDERING CODE

MODEL

**DDMX-RGBW**

DDMX-RGBW - DMX decoder

Translates controller DMX512 programs for RGB and white LED strips.

Unique DMX address for the decoder can be set easily and displayed by the numeric display on the case. Changing and resetting the DMX address requires manual input.

Use power repeater to expand output.

### Operating Voltage

12-36 VDC

### Power Capacity

up to 96W at 24V

### Operating Temperature Range

from -4°F to +122°F in case

## Smart Pixel Decoder

SPI signal to DMX signal decoder



Model

**SR-DMX-SPI**

SR-DMX-SPI - Smart Pixel Decoder

The SR-DMX-SPI is a smart LED pixel decoder that controls RGB/RGBW pixel LED strips with SPI signal. Designed with an OLED backlit panel, the pixel controller allows for easy configuration of most settings. Four push buttons are available for control of the LED functions.

\*For pixel only.

### Features

- 2 in 1 in-Wall Controller: DMX Control or Wireless RGB-W
- SPI signal output for RGB/RGBW pixel light control
- DMX512 controllable and RF/WIFI remote controllable
- Capable of addressing up to 1020 RGB pixels & 765 RGB pixels
- OLED panel allows for easy configuration

### Operating Voltage

12 - 36V DC

### Power capacity

up to 96W at 24V

### Operating temperature range

from -4°F to +122°F in case