

Kendo Closet Rod - Installation Instructions

Models KCR-

Please read all instructions prior to installation and keep for future reference!

1. Product to be installed by a qualified electrician.
2. Must be installed per NFPA 70, article 410.16.
3. Prior to installation ensure power is off at fuse box to prevent electrical shock.
4. Damp locations only.
5. Use only with Class 2 power unit.
6. Suitable for installation within the closet storage space.
7. Max 25 pounds per 6 inch with mounting supports.



luminii

7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

Page 1 of 2

1

support bracket
extrusion
every 20"
mounting end cap
1.1
1.2
1.3
support bracket
extrusion
film

1.1 Slide the support brackets into the Kendo Closet Rod extrusion. Must be installed every 20" for proper weight support distribution.

1.2 Carefully remove the protective film from the diffuser.

1.3 Push the mounting end cap onto each Kendo Closet Rod extrusion end.

2

lead wires
LED
mounting end cap
drywall
wood block
support bracket
screw
mounting end cap
screw
2.1
2.2
2.3

2.1 Run the lead wires (or DC quick connect cable) through opening in mounting surface to the remote power supply.

2.2 *Mounting surface must be flat and structurally sound.* Secure each support bracket into the mounting surface with the appropriate hardware every 20". *Diffuser lens must be in the down position.*

2.3 Remove the covers on each mounting endcap, orientate two of the three mounting holes in the up position. Followed by securing each endcap into the surface. Using the appropriate hardware.

3a

Class II power supply
120 VAC
24 VDC
power to 24 VDC Kendo Closet Rod light fixture
3a

Lead wire power feed

3a Ensure power is off to power supply! Then proceed to connect Kendo Closet Rod LED lead wires to power supply. For wiring instructions please refer to power supply wiring instructions. See page 2 - step 4 - for quick connect power feeding.

See page 2 - step 3b - for quick connect power feeding

Kendo Closet Rod - Installation Instructions

Models KCR-

Please read all instructions prior to installation and keep for future reference!

1. Product to be installed by a qualified electrician.
2. Must be installed per NFPA 70, article 410.16.
3. Prior to installation ensure power is off at fuse box to prevent electrical shock.
4. Damp locations only.
5. Use only with Class 2 power unit.
6. Suitable for installation within the closet storage space.
7. Max 25 pounds per 6 inch with mounting supports.



7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com



Page 2 of 2

