5. CATENARY MOUNT ONLY

Models: Plexineon Vertical Rings Catenary Mount Static Color

## Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.

2. USE ONLY WITH CLASS 2 POWER UNIT

3. 24 VOLTS DC

4. SUITABLE FOR WET LOCATIONS



REVO.1 10252022

1/5





Models: Plexineon Vertical Rings Catenary Mount Static Color

## Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.

2. USE ONLY WITH CLASS 2 POWER UNIT

**3.** 24 VOLTS DC


4. SUITABLE FOR WET LOCATIONS




Niles, IL 60714 T 224.333.6033 F 224.757.7557 info@luminii.com www.luminii.com

REVO.1 10252022

2/5



5. CATENARY MOUNT ONLY



Models: Plexineon Vertical Rings Catenary Mount Static Color

#### Please read all instructions prior to installation and keep for future reference!

- 1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.
- 2. USE ONLY WITH CLASS 2 POWER UNIT
- 3. 24 VOLTS DC
- 4. SUITABLE FOR WET LOCATIONS


5. CATENARY MOUNT ONLY




REVO.1 10252022

3 / 5

Joy lumini 7777 Merrimac Ave Niles, IL 60714 T 224.333.6033 F 224.757.7557 info@luminii.com www.luminii.com



- A.1 Make an U shape with mounting clip installation tool, insert two edges into mounting clip. Place plexineon fixture insde the shape. Then push the fixture into clip.
- **A.2** Remove the tool. Make sure mounting clip is clipped right on the grip.



Models: Plexineon Vertical Rings Catenary Mount Static Color

### Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.

2. USE ONLY WITH CLASS 2 POWER UNIT

4. SUITABLE FOR WET LOCATIONS

**3.** 24 VOLTS DC


5. CATENARY MOUNT ONLY



7777 Merrimac Ave Niles, IL 60714 REVO.1 10252022


4/5





**NOTE:** Catenary cables are provided by others. Max Ø1/4".

4.1 Place the catenary cable between the saddle and u-bolt. Use locknuts to clamp the catenary cable between the saddle and u-bolt.



Loosen the top locknut on back of the collar to adjust the angle of plexineon fixture.

Models: Plexineon Vertical Rings Catenary Mount Static Color

### Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.

2. USE ONLY WITH CLASS 2 POWER UNIT

**3.** 24 VOLTS DC


4. SUITABLE FOR WET LOCATIONS



REVO.1 10252022

5/5

7777 Merrimac Ave Niles, IL 60714 T 224.333.6033 F 224.757.7557 info@luminii.com www.luminii.com



5. CATENARY MOUNT ONLY

